

TPWLK

TPWLK "LOGISTIC" SERIES PALLET TRUCK SCALE



Pallet truck scales, with built-in electronic weighing, which are reliable, easy to use, suitable for harsh work conditions. These are essential for one who needs to weigh accurately but save time also. Fitted with rechargeable extractable battery. Available also with a built-in printer as well as CE-M DOUBLE RANGE approved.

Working in cooperation with:

TEGRA SYSTEMS B.V.

HANDELSWEG 7 - 1693 - AZ WERVERSHOOF - NETHERLANDS
Tel. 0031-228-582780 Fax. 0031-228-584859
info@tegrasystems.nl

**The best solution
for advanced industrial
applications**

MAIN FEATURES

- Maximum lifting capacity: 2000 kg.
- Accuracy: +/- 0.1% of the maximum capacity in the versions for internal use.
- Accuracy: +/- 0.05% of the maximum capacity in the "M" approved versions.
- Fork dimensions 1150 x 550 x 85 mm.
- Weighs about 125 kg.
- Structure in extra thick steel and oven-fire painted mechanics.
- Steering wheels and double loading poliurethane rollers.
- 4 stainless steel IP68 load cells for the legal for trade use version, aluminium IP67 load cells for the internal use version.
- Weight indicator in IP65 STAINLESS STEEL waterproof case, easy to clean and resistant to harsh and corrosive environments; large 25mm LCD display high contrast digits, which are clearly visible even in poor lighting conditions and with low temperatures, and waterproof membrane keyboard, with 17 functional keys.
- Configuration, calibration and diagnostics from keyboard or PC with DINITOOLS.
- Power supply through extractable rechargeable battery mounted on the pallet truck column.
- The operating time is of about 80 hours of continuous use or one month with the tipycal non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function.
- Battery level indication.
- Equipped with 230Vac 50 Hz battery charger.
- Configurable RS232/C bidirectional port for connection to a printer, with customisable print format.
- Configurable RS232/C bidirectional port for PC, modem radio or portable terminal.
- IR input for remote control management.
- Fitted with thermal printer in the TPWLKP and TPWLKPM versions, with Date&Time card.

MAIN FUNCTIONS

- Zeroing, Tare, Printing
- High Resolution Weighing x 10
- Net/Gross or lb/kg conversion
- Accumulation
- Formulation
- +/- Checkweighing
- Percentage weighing
- Counting (Max. resolution of 1.500.000 divisions)
- Hold and Peak

AVAILABLE UPON PRICE ESTIMATE

- Special steering wheels.
- 680 mm fork width.
- Special fork length from 850 to 1500 mm.
- Special capacity e/o divisions.
- High resolution.

VERSIONS

Versioni disponibili

Codice	Max (kg)	d (kg)	M (kg)
TPWLK-4	500 / 1000 / 2000	0,2 / 0,5 / 1	--
TPWLKM-4 M	1000 / 2000	--	0,5 / 1
TPWLKP-4	500 / 1000 / 2000	0,2 / 0,5 / 1	--
TPWLKPM-4 M	1000 / 2000	--	0,5 / 1

NOTA: colonna e timone da montare.



www.diniargeo.com



“YOUR WORLDWIDE PARTNER FOR WEIGHING”

DINI ARGEO
FRANCE sarl
Nogent-sur-Marne

DINI ARGEO
GMBH
Sinsheim - Germany

DINI ARGEO
UK Ltd
Taunton - United Kingdom

DINI ARGEO WEIGHING
INSTRUMENTS Ltd
Shanghai - China

DINI ARGEO
WEIGHBRIDGES
Calto (RO) – Italy



HEAD OFFICE
Via Della Fisica, 20
41042 Spezzano di Fiorano Modena - Italy



TEGRA SYSTEMS B.V.

HANDELSWEG 7 - 1693 - AZ WERVERSHOOF - NETHERLANDS

Tel. 0031-228-582780 Fax. 0031-228-584859

info@tegrasystems.nl

SALES AND TECHNICAL ASSISTANCE SERVICE