

# **TPWA**

### TPWA "ACTIVITY" SERIES PALLET TRUCK SCALE



Pallet truck scale supplied with new <u>DFW series</u> integrated weighing indicator. The new program allows the user to easily access to main software functions and weighing operations. TPWA's flexibility makes them indispensable in harsh working environments for anyone who needs to weigh accurately any type of product on a pallet. Available also CE-M APPROVED.

#### Working in cooperation with:

#### **MAIN FEATURES**


- Maximum lifting capacity: 2000 kg.
- Accuracy: +/- 0.1% of the maximum capacity in the versions for internal use.
- Accuracy: +/- 0.05% of the maximum capacity in the "M" approved versions.
- Weighs about 125 kg. Fork dimensions 1150 x 550 x 85 mm.
- Bearing structure in extra thick sheet steel and oven-fire painted interior construction.
- Standard fitted with +/-160° swivelling column head.
- Steering wheels and double loading rollers with a poliurethane coating.
- 4 stainless steel IP68 load cells for the legal for trade use version, aluminium IP67 load cells for the internal use version.
- Indicator with easy to clean ABS waterproof IP65 enclosure built to withstand humid and dusty environments; large LCD display 25-mm high contrast digits which are clearly visible even in poor lighting conditions; 17-key numerical/functional waterproof keyboard.
- Calibration and Set-Up configurable from keyboard or from PC with DINITOOLS.
- Power supply through built-in extractable rechargeable battery. Fitted with battery charge.
- 60-hour approximate operating time or three months with the tipycal non continuous use, thanks to its auto switch-off function.
- Programmable auto power saving function. Low Battery Warning.
- Equipped with 230Vac 50 Hz battery charger.
- Bi-directional RS232/C port configurable for connection to printer.
- Bi-directional RS232/C serial output for radio modem, PC or portable terminal.
- Fitted with thermal printer, with Date&Time card.

#### **AVAILABLE UPON PRICE ESTIMATE**

- Special steering wheels.
- 680 mm fork width.
- Special fork length from 850 to 1500 mm.
- Special capacity e/o divisions.
- · High resolution.

DETAIL 1	DETAIL 2







Closed Forks underside, for a higer protection against dirt.

# DETAIL 3



Extractable rechargeable battery.

### **VERSIONS**

Versioni disponibili			
	Max	d	M
Codice	(kg)	(kg)	(kg)

TPW20AP-2 500 / 1000 / 2000 0,2 / 0,5 / 1

TPW20APM-2 M 1000 / 2000 0,5 / 1





DINI ARGEO FRANCE sarl Nogent-sur-Marne DINI ARGEO **GMBH** Sinsheim - Germany DINI ARGEO UK Ltd

Taunton - United Kingdom

DINI ARGEO WEIGHING INSTRUMENTS Ltd Shanghai - China

DINI ARGEO WEIGHBRIDGES Calto (RO) - Italy



**HEAD OFFICE** Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy







#### TEGRA SYSTEMS B.V.

HANDELSWEG 7 - 1693 - AZ WERVERSHOOF - NETHERLANDS Tel. 0031-228-582780 Fax. 0031-228-584859 info@tegrasystems.nl

SALES AND TECHNICAL ASSISTANCE SERVICE